

**MERICRUSHER**

**MJHS-241 STX**

**For versatile crushing**



**MERICRUSHER**

# MERICRUSHER

## MJHS-241 STX

# For versatile crushing

### MERICRUSHER WORKING ENVIRONMENTS

#### FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

#### AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

#### EQUIPMENT

#### FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT or UNTHRotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor
- Bolt mounted lift arm brackets

#### CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

#### OPTIONS

- Slip alarm (12V)
- Sizing screen rotating (hydraulic front/rear)
- Sizing screen door type (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- Hydraulic Top Link
- Multiple cutter options available

### Base machine demand


Tractor	
Mounting	CAT-3
Auxiliary hydraulic	3 pcs. double acting
PTO	1000 rpm
Working speed	Creeper gear recommended

### Technical data:

Power range	200 - 400 hp
Transmission	Mechanical PTO
Final transmission	Gear (X-serie)
Clutch	POC-3 XL
Rotor diameter / width	600 / 2410mm 24 / 95 inch
Cutter qty.	98 (UNTH Rotor)
Working depth	300 mm / 12 inch

### Main dimensions:

Length	2540 mm	100 inch
Width	2910 mm	115 inch
Height	1430 mm	57 inch
Weight	2500 kg	5500 lbs
Weight, with options	3700 kg	8160 lbs



SUOKONE OY  
88610 Vuokatti  
FINLAND

tel. +358 86 66 2011  
suokone@suokone.com  
www.mericrusher.com