

**MERICRUSHER**

**MJHS-311 DTG**

**For versatile crushing**



**MERICRUSHER**

# MERICRUSHER

## MJHS-311 DTG

# For versatile crushing

### MERICRUSHER WORKING ENVIRONMENTS

#### FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

#### AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

#### EQUIPMENT

#### FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT or UNTH Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor
- Bolt mounted lift arm brackets

#### CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

#### OPTIONS

- Slip alarm (12V)
- Sizing screen rotating (hydraulic front/rear)
- Sizing screen door type (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- Hydraulic Top Link
- Multiple cutter options available

### Base machine demand

Tractor	
Mounting	CAT 3
Auxiliary hydraulic	3 pcs. double acting
PTO	1000 rpm
Working speed	Creep gear recommended

### Technical data:

Power range	200 - 400 hp	
Transmission	Mechanical PTO	
Final transmission	Gear (G-serie)	
Clutch	POC-3	
Rotor diameter / width	600 / 3110mm	24 / 122 inch
Cutter qty.	130 (UNTH Rotor)	
Working depth	300 mm / 12 inch	

### Main dimensions:

Length	2540 mm	100 inch
Width	3610 mm	142 inch
Height	1430 mm	57 inch
Weight	2800 kg	6200 lbs
Weight, with options	4350 kg	9600 lbs

