

MERICRUSHER

MJHS-311 STX

For versatile crushing



MERICRUSHER

MERICRUSHER

MJHS-311 STX

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT or UNTH Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor
- Bolt mounted lift arm brackets

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

OPTIONS

- Slip alarm (12V)
- Sizing screen rotating (hydraulic front/rear)
- Sizing screen door type (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- Hydraulic Top Link
- Multiple cutter options available

Base machine demand

| | |
|---------------------|--------------------------|
| Tractor | |
| Mounting | CAT-3 |
| Auxiliary hydraulic | 3 pcs. double acting |
| PTO | 1000 rpm |
| Working speed | Creeper gear recommended |

Technical data:

| | |
|------------------------|---------------------------------|
| Power range | 200 - 400 hp |
| Transmission | Mechanical PTO |
| Final transmission | Gear (X-serie) |
| Clutch | POC-3 XL |
| Rotor diameter / width | 600 / 3110mm 24 / 122 inch |
| Cutter qty. | 130 (UNTH Rotor) |
| Working depth | 300 mm / 12 inch |

Main dimensions:

| | | |
|----------------------|---------|----------|
| Length | 2540 mm | 100 inch |
| Width | 3610 mm | 142 inch |
| Height | 1430 mm | 57 inch |
| Weight | 2850 kg | 6280 lbs |
| Weight, with options | 4300 kg | 9500 lbs |



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com