

**MERICRUSHER**

**MJS-242 STG / DTG**

**For versatile crushing**



**MERICRUSHER**

# MERICRUSHER

## MJS-242 STG / DTG

# For versatile crushing

### MERICRUSHER WORKING ENVIRONMENTS

#### FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

#### CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

#### AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

#### EQUIPMENT

#### FEATURES

- Fixed counter blades
- Hardox liner welded (frame)
- UNT Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor.

#### OPTIONS

- Guide plate hydraulic (front / rear)
- Sizing screen door type hydraulic (front / rear)
- Rear roller hydraulic (long arms)
- Hydraulic Top Link
- Multiple cutter options available

### Base machine demand

Tractor	
Mounting	CAT-3
Auxiliary hydraulic	3 pcs. double acting
PTO	1000 rpm
Working speed	Creep gear recommended

### Technical data:

Power range STG / DTG	120 - 240 hp	150 - 300 hp
Transmission	Mechanical PTO	
Final transmission	Gear (G-serie)	
Clutch	POC-3	
Rotor diameter / width	500 / 2400mm	20 / 95 inch
Cutter qty.	102 (UNT Rotor)	
Working depth	250 mm / 10 inch	

### Main dimensions:

Length	2010 mm	79 inch
Width STG / DTG	2800 / 2850 mm	110 / 112 inch
Height	1310 mm	52 inch
Weight ST / DT	1570 / 1810 kg	3460 / 3990 lbs
Weight, with options ST / DT	2220 / 2460 kg	4900 / 5420 lbs



SUOKONE OY  
88610 Vuokatti  
FINLAND

tel. +358 86 66 2011  
suokone@suokone.com  
www.mericrusher.com