

**MERICRUSHER**

**MJS-244 STG / DTG**

**For versatile crushing**



**MERICRUSHER**



# MERICRUSHER

## MJS-244 STG / DTG

# For versatile crushing

### MERICRUSHER WORKING ENVIRONMENTS

#### FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

#### CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

#### AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

#### EQUIPMENT

#### FEATURES

- Bolted adjustable counter blades
- Hardox liner in frame (bolted)
- UNT Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor.
- Bolted lift arm brackets

#### OPTIONS

- Guide plate hydraulic (front / rear)
- Sizing screen door type hydraulic (front / rear)
- Rear roller hydraulic (long arms)
- Hydraulic Top Link
- Multiple cutter options available

### Base machine demand

Tractor	
Mounting	CAT-3
Auxiliary hydraulic	3 pcs. double acting
PTO	1000 rpm
Working speed	Creep gear recommended

### Technical data:

Power range STG / DTG	120 - 240 hp	150 - 300 hp
Transmission	Mechanical PTO	
Final transmission	Gear (G-serie)	
Clutch	POC-3	
Rotor diameter / width	500 / 2400mm	20 / 95 inch
Cutter qty.	102 (UNT Rotor)	
Working depth	250-300 mm / 10-12 inch	

### Main dimensions:

Length	2050 mm	81 inch
Width STG / DTG	2815 / 2835 mm	112 / 113 inch
Height	1360 mm	54 inch
Weight STG / DTG	1650 / 1890 kg	3640 / 4170 lbs
Weight, with options STG / DTG	2300 / 2540 kg	5070 / 5600 lbs



SUOKONE OY  
88610 Vuokatti  
FINLAND

tel. +358 86 66 2011  
suokone@suokone.com  
www.mericrusher.com