

MERIROAD
RC-4220 ST / DT

For crushing roads



MERIROAD

MERIROAD

RC-4220 ST / DT

For crushing roads

MERIROAD WORKING ENVIRONMENTS

ROAD CONSTRUCTION

- Gravel road maintenance
- Preparing of hauling lines
- Maintenance of forest roads
- Ice and hard packed snow removal from roads, side walks, intersections, parking areas

EQUIPMENT

FEATURES

- Bolted counter blades
- Hardox liner (frame)
- STD or STE Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented) or FT-44 safety clutch
- Possibility to turn the direction of the rotor

OPTIONS

- POC - safety clutch (patented)
- Support wheels
- Rear belt
- Hydraulic Top Link
- Rear support skids
- Front plate (UP-Rotation)

Base machine demand

Four wheel tractor	
Mounting	CAT 2
Auxiliary hydraulic	1 pcs. 2-way
PTO	(540)/1000 rpm
Working speed	Creep gear recommended

Technical data:

Power range	90 - 180 hp
Transmission	Mechanical PTO
Final gear	Chain gear 2-row
Clutch	POC-2 or FT44
Rotor diam / width	400 / 2250mm 16 / 89 inch
Cutter qty.	96 (T25 Rotor)
Working depth	200 mm / 8 inch

Main dimensions:

Lenght	1550 mm	61 inch
Widht	2700 mm	106 inch
Height	1220 mm	48 inch
Weigth ST / DT	930 / 1080 kg	2050 / 2400 lbs
Weigth, with options	1290 / 1440 kg	2850 / 3200 lbs

